



**SPECIFICATIONS  
COMMERCIAL HEAT RECOVERY VENTILATOR**

**Model  
SHRV2500DD**

<b>OPTIONS INSTALLED:</b>	<b>Damper Defrost</b>	<b>CASE:</b>	18 gauge painted Galvanized.
<b>ELECTRICAL:</b>	230/1/60 208/3/60 230/3/60 460/3/60 575/3/60	<b>SHIPPING WEIGHT:</b>	750 pounds
<b>MOTORS:</b>	As specified per unit 1 HP 230/1/60    2 HP 208/3/60 1 HP 208/3/60    2 HP 230/3/60 1 HP 230/3/60    2 HP 460/3/60 1 HP 460/3/60    2 HP 575/3/60 1 HP 575/3/60	<b>INSULATION:</b>	2" thick scrim faced fibre glass insulation.
<b>FANS:</b>	Centrifugal type; Each air stream has one fan and motor assembly	<b>CONTROL:</b>	Electronic printed circuit board. External low voltage controls ( 24 vac ) External power strip for dehumidistat  Defrost LED indicates when defrost cycle is active.
<b>MOUNTING:</b>	Base rails are equipped with mounting holes for lifting lugs and suspension rods.	<b>CORE:</b>	Three, easily accessed for cleaning. Polypropylene – plate to plate.
<b>DRAIN CONNECTIONS:</b>	2 @ 3/4" diameter	<b>FILTERS:</b>	Exhaust and Supply air streams 4" thick pleated.

All dimensions are in inches

