

# SUPERVENTOR 100T



*Built Better To Last Longer*



# CONSTANT FRESH AIR...

- 1 Color coded collars easily identify top discharge intake and exhaust ports.
- 2 Attractive prefinished insulated cabinet: Provides structural strength and quiet operation.
- 3 High efficiency coroplast core: Provides one of the best transfer rates in the industry up to 87%. The heat exchange core is easy to clean and does not contribute to mold growth.
- 4 Built in dehumidistat: Automatically controls excess humidity.
- 5 Energy efficient motors ensure years of low cost operation with minimum maintenance.
- 6 State-of-the-art recirculating damper defrost system: Eliminates the possibility of core freeze up and negative pressure.
- 7 Permanent washable filters: Filters both incoming and exhaust air to remove additional air borne contaminants before they're allowed to enter the home.
- 8 3 speed built-in fan control corrects changes in ventilation levels without any additional controls.
- 9 Illuminated "ON/OFF" switch.
- 10 Complete range of optional remote controls.
- 11 Integral Balancing Dampers.
- 12 Connections for external fan interlock.



Specifications	
Description	SHRV 100T
Length	27 5/8
Width	21 3/8
Height	18 3/4
VAC @ 60 Hz	120
Amps	2
Shipping Weight Lbs	80
Airflow	C.F.M. Against External Static Pressure (each air stream)
.7"	64
.6"	68
.5" (125 Pa)	72
.4" (100 Pa)	78
.3" (75 Pa)	83
.2" (50 Pa)	87
.1" (25 Pa)	92
Built in Dehumidistat	Yes
Sensible Effectiveness	87%

### Lifetime Warranty:

Limited Lifetime Warranty on heat exchange core and full five year warranty on electrical components.  
All models CSA approved.

### Distributed By:



PRINTED IN CANADA

Canada Patent Registration 052580451  
U.S. Pat Pend  
Application# 10-712681



Summaira Mfg.  
Peterborough, ON. Canada K9J 7B1  
(705)745-4736